

PDB-電源分配模組 Power Distribution Blocks

產品特色



- High SCCR 200kA
- 取代傳統銅條式安裝
- DIN導軌、面板安裝節省空間與時間
- 組合範圍多種規格選擇
- 額定電壓: 600Vac/dc
- 額定電流: 175A ~ 310A
- 符合多項認證: UL、CSA®、CE
- 防燃等級: UL 94-V0
- 工作溫度範圍: -20°C ~ 120°C

接線方式




1進-4出

PDB220-1	170A	1Pole
PDB220-3	170A	3Pole




1進-6出

PDB321-1	170A	1Pole
PDB321-2	170A	2Pole
PDB321-3	170A	3Pole
PDB323-1	310A	1Pole
PDB323-3	310A	3Pole



1進-9出

PDB371-1	310A	1Pole
PDB371-3	310A	3Pole



1進-12出

PDB370-1	310A	1Pole
PDB370-3	310A	3Pole

PDBFS-防觸型電源分配模組

Power Distribution Blocks Finger-Safe

產品特色



- High SCCR 200kA
- 取代傳統銅條式安裝
- DIN導軌、面板安裝節省空間與時間
- 組合範圍多種規格選擇
- 可組裝多Pole(2P、3P、4P)
- 額定電壓: 600Vac/dc
- 額定電流: 175A ~ 760A
- 符合多項認證: UL、CSA®、CE
- 防燃等級: UL 94-V0
- 工作溫度範圍: -20°C ~ 120°C
- IP-20防觸安全

接線方式



1進-4出

PDBFS220


175A



1進-6出

PDBFS330

380A



2進-12出

PDBFS377

570A



2進-2出

PDBFS500

620A

PDBFS504

760A

*提高安全性、美觀並且符合規範

