## **DATASHEET - 10731885**



## Fuse, 25A, AC 550 V, V88/A2, 14 x 85 mm, gL/gG

## AA025

Similar to illustration

| Product name           | Eaton Bussmann series low voltage british standard fuse |
|------------------------|---|
| Part no.               | AA025   |
| EAN                    | 5027590491549   |
| Product Length/Depth   | 85 millimetre   |
| Product height         | 14 millimetre   |
| Product width          | 14 millimetre   |
| Product weight         | 20.1 gram   |
| Compliances            | RoHS Compliant  |
| Product Tradename      | None  |
| Product Type           | Low voltage british standard fuse                       |
| Product Sub Type       | None  |
| Electrical data        |   |
| Amperage Rating        | 25 A  |
| Voltage rating         | 550 V   |
| Breaking capacity      | 80 kA   |
| Class                  | Class gG/gL   |
| Product specifications |   |
| Application            | general industrial applications                         |
| Fuse type              | AAO   |
| Fuse size              | BS88/A2   |
| Fitted with:           | Offset bolted tags                                      |
| Connection             | 73 mm fixing centre                                     |
| Quantity               | 20  |
| Compatible fuse holder |   |
| Suitable for           | RS32 Red spot fuse holder<br>CM32F Camaster fuse holder |

## **Technical data ETIM 9.0**

| Circuit breakers and fuses (EG000020) / HRC fuse (EC004556)  |  |    |  |  |  |  |
|--|--|----|--|--|--|--|
| Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Safety fuse inserts (unspecified) (ecl@ss13-27-14-20-90 [BAB264016]) |  |    |  |  |  |  |
| Fuse system according to IEC 60269   |  |    | Fuse system E                              |  |  |  |
| Fuse construction type according to IEC 60269  |  |    | A2   |  |  |  |
| Type of current  |  |    | AC   |  |  |  |
| Rated voltage AC   |  | V  | 550  |  |  |  |
| Rated voltage DC   |  | V  |  |  |  |  |
| Rated current  |  | Α  | 25   |  |  |  |
| Utilization category   |  |    | gG (cable protection/equipment protection) |  |  |  |
| Breaking capacity  |  | kA | 80   |  |  |  |
| Colour code  |  |    | None                                       |  |  |  |
| Type of fuse status indicator  |  |    | None                                       |  |  |  |
| Power loss at rated current  |  | W  | 2.1  |  |  |  |
| Mounting holes   |  |    | M5   |  |  |  |
| Centre-to-centre distance of connections   |  | mm | 73   |  |  |  |