## **DATASHEET - FUSE 500A 690V DIN 2 GR**



Fuse-link, high speed, 500 A, AC 690 V, DIN 2, 60 x 74 x 150 mm, gR, DIN, IEC, single indicator



Part no. FUSE 500A 690V DIN 2 GR 170M5887

| eneral specifications |                                                                      |
|-----------------------|----------------------------------------------------------------------|
| Product name          | Eaton Bussmann series high speed square body fuse                    |
| Part no.              | FUSE 500A 690V DIN 2 GR                                              |
| EAN                   | 5027590461160                                                        |
| Product Length/Depth  | 210 millimetre                                                       |
| Product height        | 80 millimetre                                                        |
| Product width         | 160 millimetre                                                       |
| Product weight        | 424 gram                                                             |
| Compliances           | CE<br>RoHS Compliant<br>EAC                                          |
| Certifications        | IEC 60269-4                                                          |
| Product Tradename     | None                                                                 |
| Product Type          | High speed square body fuse                                          |
| Product Sub Type      | None                                                                 |
| lectrical data        |                                                                      |
| Amperage Rating       | 500 A                                                                |
| Voltage rating        | 690 V (IEC)                                                          |
| Interrupt rating      | 200 kAIC                                                             |
| Class                 | Class gR                                                             |
| roduct specifications |                                                                      |
| Application           | Semiconductor, DC Common bus, DC drives, power converters/rectifiers |
| Fuse type             | DIN 43620<br>T indicator for micro<br>Bladed                         |
| Fuse indicator        | Top fuse status indicator                                            |
| Fuse size             | 2                                                                    |

## **Technical data ETIM 9.0**

| Circuit breakers and fuses (EG000020) / HRC fuse (EC004556)                   |                          |               |                                                                               |  |  |
|-------------------------------------------------------------------------------|--------------------------|---------------|-------------------------------------------------------------------------------|--|--|
| Electric engineering, automation, process control engineering / Electrical in | nstallation, device / Sa | ıfety fuse ir | nserts / Safety fuse inserts (unspecified) (ecl@ss13-27-14-20-90 [BAB264016]) |  |  |
| Fuse system according to IEC 60269                                            |                          |               | Other                                                                         |  |  |
| Fuse construction type according to IEC 60269                                 |                          |               | 2                                                                             |  |  |
| Type of current                                                               |                          |               | AC                                                                            |  |  |
| Rated voltage AC                                                              |                          | V             | 690                                                                           |  |  |
| Rated voltage DC                                                              |                          | V             |                                                                               |  |  |
| Rated current                                                                 |                          | Α             | 500                                                                           |  |  |
| Utilization category                                                          |                          |               | aR (accompanied semiconductor protection)                                     |  |  |
| Breaking capacity                                                             |                          | kA            | 200                                                                           |  |  |
| Colour code                                                                   |                          |               | None                                                                          |  |  |
| Type of fuse status indicator                                                 |                          |               | Top fuse status indicator                                                     |  |  |
| Power loss at rated current                                                   |                          | W             | 66                                                                            |  |  |
| Mounting holes                                                                |                          |               |                                                                               |  |  |
| Centre-to-centre distance of connections                                      |                          | mm            |                                                                               |  |  |