

Eaton 170M4467

Fuse-link, high speed, 700 A, AC 690 V, size 1, aR, IEC, UL, single indicator

IEC Rated



defaultTaxonomyAttributeLabel

Type

Fuse

Application

Semiconductor, DC Common bus, DC drives, power converters/rectifiers

Amperage Rating

700 A

Breaking capacity

200 kA

Fuse indicator

Centre fuse status indicator

Insulated metal gripping lugs (IMGL)

No

Utilization category

aR (accompanied semiconductor protection)

Voltage type

AC

Fuse size

1

Rated voltage AC

690 V

Center-to-center distance of connections

51.1 mm

Current type

AC

Mounting dimension

M8

Class

Class aR

Clearing (I₂T)

465000 at 660 V

Watt losses

85 W

Fuse shape

Square body, flush end contacts

Resources

Catalogs

[eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf](#)

[170M4467~Eaton Bussmann series high speed square body fuse](#)

[Bussmann series complete full line catalog no. 1007](#)

Compliance information

[UKCA Fuse-links for the protection of semiconductor devices, Size 1 up to 900A](#)

[CE Fuse-links for the protection of semiconductor devices, Size 1 up to 900A](#)

Pre arc (I2T)

69500

Color

None

Interrupt rating

200 kAIC

Fitted with:

Type K Indicator for micro

Construction size

1

Mounting method

Flush

Packaging type

Standard

Voltage rating

690 V (IEC), 700 V (UL)

Fuse type

Flush end

BKN/Type K Indicator for Micro

Fuse system (according to IEC 60269)

IEC 60269-4 flush end connections type A



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia