



Fuse-link, high speed, 500 A, AC 690 V, size 2, 61 x 77 x 135 mm, aR, IEC, UL, single indicator

170M5760

Similar to illustration

General specifications		
Product name		Eaton Busmann series high speed square body fuse
Part no.		170M5760
EAN		5027590458443
Product Length/Depth		168 millimetre
Product height		80 millimetre
Product width		124 millimetre
Product weight		321 gram
Compliances		CE Marked RoHS Compliant
Certifications		UL Recognized IEC Rated
Product Tradename		None
Product Type		High speed square body fuse
Product Sub Type		None
Electrical data		
Amperage Rating		500 A
Voltage rating		690 V
Interrupt rating		200 kAIC
Class		Class aR
Clearing (I2T)		145000 at 660 V
Product specifications		
Application		Semiconductor, DC Common bus, DC drives, power converters/rectifiers
Fuse type		US Style FKE/115 Type K indicator for micro Bolted tag
Fuse indicator		Centre fuse status indicator
Fuse size		2

Technical data ETIM 9.0

Circuit breakers and fuses (EG000020) / HRC fuse (EC004556)		
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Safety fuse inserts (unspecified) (ecl@ss13-27-14-20-90 [BAB264016])		
Fuse system according to IEC 60269		Other
Fuse construction type according to IEC 60269		2
Type of current		AC
Rated voltage AC	V	690
Rated voltage DC	V	
Rated current	A	500
Utilization category		aR (accompanied semiconductor protection)
Breaking capacity	kA	200
Colour code		None
Type of fuse status indicator		Centre fuse status indicator
Power loss at rated current	W	75
Mounting holes		M12
Centre-to-centre distance of connections	mm	114