

DATASHEET - FUSE 315A 690V DIN 2 GR



Fuse-link, high speed, 315 A, AC 690 V, DIN 2, 60 x 74 x 150 mm, gR, DIN, IEC, single indicator

Part no. FUSE 315A 690V DIN 2 GR
170M5883

Similar to illustration

General specifications		
Product name		Eaton Bussmann series high speed square body fuse
Part no.		FUSE 315A 690V DIN 2 GR
EAN		5027590461115
Product Length/Depth		210 millimetre
Product height		80 millimetre
Product width		160 millimetre
Product weight		477 gram
Compliances		CE Marked RoHS Compliant
Certifications		IEC Rated UL Recognized
Product Tradename		None
Product Type		High speed square body fuse
Product Sub Type		None
Electrical data		
Amperage Rating		315 A
Voltage rating		690 V (IEC)
Interrupt rating		200 kAIC
Class		Class gR
Clearing (I ₂ T)		105000 at 600 V
Product specifications		
Application		Semiconductor, DC Common bus, DC drives, power converters/rectifiers
Fuse type		DIN 43620 T indicator for micro Bladed
Fuse indicator		Top fuse status indicator
Fuse size		2

Technical data ETIM 9.0

Circuit breakers and fuses (EG000020) / HRC fuse (EC004556)		
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Safety fuse inserts (unspecified) (ecl@ss13-27-14-20-90 [BAB264016])		
Fuse system according to IEC 60269		Other
Fuse construction type according to IEC 60269		2
Type of current		AC
Rated voltage AC	V	690
Rated voltage DC	V	
Rated current	A	315
Utilization category		aR (accompanied semiconductor protection)
Breaking capacity	kA	200
Colour code		None
Type of fuse status indicator		Top fuse status indicator
Power loss at rated current	W	46
Mounting holes		
Centre-to-centre distance of connections	mm	