## **DATASHEET - 21300905**



## Fuse-link, high speed, 550 A, AC 2500 V, size 3, 86 x 95 x 166 mm, aR, IEC, single indicator

## 170M6643

| General specifications |   |
|------------------------|---|
| Product name           | Eaton Bussmann series high speed square body fuse |
| Part no.               | 170M6643  |
| EAN                    | 5027590463133                                     |
| Product Length/Depth   | 108 millimetre                                    |
| Product height         | 180 millimetre                                    |
| Product width          | 250 millimetre                                    |
| Product weight         | 251 gram  |
| Certifications         | IEC 60269-4                                       |
| Product Tradename      | None  |
| Product Type           | High speed square body fuse                       |
| Product Sub Type       | None  |
| Electrical data        |   |
| Amperage Rating        | 550 A   |
| Voltage rating         | 2500 V  |
| Interrupt rating       | 100 kAIC  |
| Class                  | Class aR  |
| Product specifications |   |
| Application            | semiconductor protection                          |
| Fuse type              | Flush end   |
| Fuse indicator         | Centre fuse status indicator                      |
| Fuse size              | 3   |

## **Technical data ETIM 9.0**

| Circuit breakers and fuses (EG000020) / HRC fuse (EC004556)                             |                           |  |  |  |
|---|---------------------------|--|--|--|
| Electric engineering, automation, process control engineering / Electrical installation | n, device / Safety fuse i | inserts / Safety fuse inserts (unspecified) (ecl@ss13-27-14-20-90 [BAB264016]) |  |  |
| Fuse system according to IEC 60269  |                           | IEC 60269-4 flush end connections type A                                       |  |  |
| Fuse construction type according to IEC 60269   |                           | 3  |  |  |
| Type of current   |                           | AC   |  |  |
| Rated voltage AC  | V                         | 2500   |  |  |
| Rated voltage DC  | V                         |  |  |  |
| Rated current   | Α                         | 550  |  |  |
| Utilization category  |                           | aR (accompanied semiconductor protection)                                      |  |  |
| Breaking capacity   | kA                        | 100  |  |  |
| Colour code   |                           | None   |  |  |
| Type of fuse status indicator   |                           | Centre fuse status indicator   |  |  |
| Power loss at rated current   | W                         | 175  |  |  |
| Mounting holes  |                           | M12  |  |  |
| Centre-to-centre distance of connections  | mm                        | 166  |  |  |
|   |                           |  |  |  |