

Features

- ✧ 17.5mm dual-side LCD display
- ✧ M1~M8 pre-set memory key for saving unit price
- ✧ 99 sets of indirect PLU
- ✧ Give-change function
- ✧ Weight Unit: kg/100g available
- ✧ Auto Zero Point Tracking
- ✧ Gravity-value setting
- ✧ External Digital-Calibration
- ✧ Stainless steel platter
- ✧ Low power & charging status indication
- ✧ Dimension:
Scale: 300 x 316 x 100 mm (WxDxH)
Platter: 295 x 215 mm (WxD)



Specifications:

Model	Capacity	Division
QEP-6	6kg	1g/2g
QEP-15	15kg	2g/5g
QEP-30	30kg	5g/10g

Option:

1. Backlight for rear display
2. RS-232 or Relay output

Power Source:

DC: 4Ah/6V Rechargeable battery
(160hr without backlight)
AC: 110V or 220V $\pm$ 10%, 50/60Hz

◆ Above is made in China

Features

- ✧ 17.5mm dual-side LCD display
- ✧ M1~M8 pre-set memory key for saving unit price
- ✧ 99 sets of indirect PLU
- ✧ Give-change function
- ✧ Weight Unit: kg/100g available
- ✧ Auto Zero Point Tracking
- ✧ Gravity-value setting
- ✧ External Digital-Calibration
- ✧ Stainless steel platter
- ✧ Low power & Charging status Indication
- ✧ Dimension:
Scale: 300 x 316 x 100 mm (WxDxH)
Platter: 295 x 215 mm (WxD)



Option:

1. Backlight for rear display
2. RS-232 or Relay output Interface

Specifications:

Model	Capacity	Division
QEPL-6	6kg	1g/2g
QEPL-15	15kg	2g/5g
QEPL-30	30kg	5g/10g

Power Source:

DC: 4Ah/6V Rechargeable battery
(160hr without backlight)

AC: 110V or 220V $\pm$ 10%, 50/60Hz

◆ Above is made in China