



SENTRON, Fuse switch disconnecter 3NP1, 3-pole, NH00, 160 A, for assembly and installation on mounting plate, flat terminal, Cover level 45 mm

| Model | |
|--|---|
| product brand name | SENTRON |
| product designation | 3NP1 fuse switch disconnecter |
| design of the product | cover level 45 mm |
| design of the safety monitoring | Without |
| design of the actuating element | Cover handle |
| design of the load switch / strip form | No |
| type of the driving mechanism / motor drive | No |
| General technical data | |
| number of poles | 3 |
| type of device | For assembly and installation on mounting plate |
| size of disconnecting link | 00 and 000 |
| size of fuse link | NH000, NH00 |
| let-through current / with closed switch / maximum permissible | 23 kA |
| mechanical service life (switching cycles) / typical | 2 000 |
| power factor | |
| • at AC-22 B | 0.65 |
| • at AC-23 B | 0.45 |
| • with capacitive load | -0.25 |
| fuse system | LV HRC fuse |
| degree of pollution | 3 |
| Voltage | |
| insulation voltage | |
| • rated value | 690 V |
| • with degree of pollution 3 / at AC / rated value | 690 V |
| • with degree of pollution 2 / at AC / rated value | 1 000 V |
| power factor / at AC-21 B | 0.95 |
| surge voltage resistance / rated value | 8 kV |
| operating voltage | |
| • at AC / rated value / maximum | 690 V |
| • at DC / rated value | 440 V |
| • at DC / rated value / maximum | 440 V |
| Protection class | |
| protection class IP | |
| • with closed switch / with cover or cable lug cover | IP40 |
| • with closed switch / without cover or cable lug cover | IP30 |
| • open | IP20 |
| • on the front | IP40 |

| Dissipation | |
|--|-------|
| power loss [W] | |
| • with conventional rated thermal current / without fuse / per pole | 5 W |
| • with conventional rated thermal current / without fuse / per device | 15 W |
| • for rated value of the current / at AC / in hot operating state / per pole | 17 W |
| • of the fuse / per fuse / maximum | 12 W |
| Current | |
| operational current | |
| • at 35 °C / rated value | 160 A |
| • at 40 °C / rated value | 155 A |
| • at 45 °C / rated value | 145 A |
| • at 50 °C / rated value | 140 A |
| • at 55 °C / rated value | 133 A |
| • at AC / rated value | 160 A |
| • at AC-23 B / at 690 V / rated value | 35 A |
| • at AC-23 B / at 500 V / rated value | 63 A |
| • at AC-23 B / at 400 V / rated value | 160 A |
| • at AC-23 B / at 240 V / rated value | 160 A |
| • at AC-22 B / at 690 V / rated value | 125 A |
| • at AC-22 B / at 500 V / rated value | 160 A |
| • at AC-22 B / at 400 V / rated value | 160 A |
| • at AC-22 B / at 240 V / rated value | 160 A |
| • at AC-21 B / at 690 V / rated value | 160 A |
| • at AC-21 B / at 500 V / rated value | 160 A |
| • at AC-21 B / at 400 V / rated value | 160 A |
| • at AC-21 B / at 240 V / rated value | 160 A |
| • at DC-23 B / at 440 V / rated value | 63 A |
| • at DC-23 B / at 240 V / rated value | 100 A |
| • at DC-23 B / at 120 V / rated value | 100 A |
| • at DC-22 B / at 440 V / rated value | 125 A |
| • at DC-22 B / at 240 V / rated value | 160 A |
| • at DC-22 B / at 120 V / rated value | 160 A |
| • at DC-21 B / at 440 V / rated value | 160 A |
| • at DC-21 B / at 240 V / rated value | 160 A |
| • at DC-21 B / at 120 V / rated value | 160 A |
| let-through current / with high-speed activation / maximum permissible | 15 kA |
| Main circuit | |
| operational current | |
| • rated value | 160 A |
| • with capacitive load / at 400 V / rated value | 72 A |
| • with capacitive load / at 500 V / rated value | 55 A |
| Auxiliary circuit | |
| number of CO contacts / for auxiliary contacts | 0 |
| number of NC contacts / for auxiliary contacts | 0 |
| number of NO contacts / for auxiliary contacts | 0 |
| Suitability | |
| suitability for use | |
| • main switch | No |
| • switch disconnecter | Yes |
| • EMERGENCY OFF switch | No |
| • safety switch | Yes |
| • maintenance/repair switch | Yes |
| Product details | |
| product feature / interlock | Yes |
| • product component / trip indicator | No |
| • product function / phase failure monitoring | No |

| | |
|---|-----|
| • product component / undervoltage release | No |
| • product component / undervoltage release with leading contact | No |
| product feature / sealable | Yes |
| product extension / auxiliary switch | Yes |
| product extension / optional | |
| • locking capability | Yes |
| • motor drive | No |
| • phase failure monitoring | Yes |
| • fuse monitoring | Yes |
| • voltage trigger | No |
| • overvoltage protection monitoring | Yes |

Product function

| | |
|-------------------------------------|----|
| product function | |
| • fuse monitoring | No |
| • overvoltage protection monitoring | No |

Connections

| | |
|--|---------------------|
| arrangement of electrical connectors / for main current circuit | other |
| connectable conductor cross-section / for main contacts | |
| • solid or stranded / minimum | 2.5 mm ² |
| • solid or stranded / maximum | 95 mm ² |
| • stranded / minimum | 2.5 mm ² |
| • stranded / maximum | 95 mm ² |
| tightening torque / with screw-type terminals | |
| • minimum | 10 N·m |
| • maximum | 12 N·m |
| type of connectable conductor cross-sections / of the laminated conductors / maximum | 24 x 12 mm |
| type of connection technology | Flat terminal |
| type of electrical connection / for main current circuit | busbar connection |

Mechanical Design

| | |
|--|---------------------|
| height | 202 mm |
| width | 105.8 mm |
| depth | 86.5 mm |
| fastening method | mounting plate |
| fastening method | |
| • floor mounting | Yes |
| • 4-hole front mounting | No |
| • front mounting with central attachment | No |
| • rail mounting | No |
| mounting position | horizontal/vertical |
| net weight | 0.73 kg |

Environmental conditions

| | |
|--|--------|
| ambient temperature / during operation | |
| • minimum | -25 °C |
| • maximum | 55 °C |
| ambient temperature / during storage | |
| • minimum | -50 °C |
| • maximum | 80 °C |

General Product Approval

[Confirmation](#)



[Miscellaneous](#)



| | | |
|---------------------------|-------------------|-------------------|
| Declaration of Conformity | Test Certificates | Marine / Shipping |
|---------------------------|-------------------|-------------------|

other

[Miscellaneous](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3NP1133-1CA10>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3NP1133-1CA10>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)


http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3NP1133-1CA10

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>



CB

