



SITOR cylindrical fuse link, 10 x 38 mm, 32 A, aR, Un AC: 600 V

| Model                                                                                       |                             |
|---------------------------------------------------------------------------------------------|-----------------------------|
| product brand name                                                                          | SETRON                      |
| product designation                                                                         | SITOR cylindrical fuse link |
| General technical data                                                                      |                             |
| operating class of the fuse link                                                            | aR                          |
| size of the fuse link                                                                       | 10x38 mm                    |
| type of voltage / of the operating voltage                                                  | AC                          |
| operating voltage / at AC / rated value                                                     | 600 V                       |
| Dissipation                                                                                 |                             |
| power loss [W] / for rated value of the current / at AC / in hot operating state / per pole | 7.5 W                       |
| operational current / at AC / rated value                                                   | 32 A                        |
| Main circuit                                                                                |                             |
| operational current / rated value                                                           | 32 A                        |
| Product details                                                                             |                             |
| product component / striker                                                                 | No                          |
| Mechanical Design                                                                           |                             |
| mounting position                                                                           | Any, preferably vertical    |
| net weight                                                                                  | 9 g                         |
| General Product Approval                                                                    |                             |



[Confirmation](#)



[Miscellaneous](#)



Declaration of Conformity

other



[Miscellaneous](#)

### Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3NC1032>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3NC1032>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=3NC1032](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3NC1032)

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>



