

## Features

- ✧ 21mm Dual-Side LCD Display (customer side and vendor side)
- ✧ With Dual-Range Division
- ✧ M1~M8, 8 sets of direct memory keys
- ✧ 90 sets of indirect PLU
- ✧ Give-Change Function
- ✧ Weight Unit: kg/ 100g available
- ✧ Auto Zero Point Tracking
- ✧ Tare Function
- ✧ Anti-Cockroach Device
- ✧ Low power & Charging status Indication
- ✧ Stainless Steel Platter
- ✧ Dimension:  
Scale: 300 x 330 x 120 mm (WxDxH)  
Platter: 300 x 240 mm (WxD)

### Option:

1. Pole Display
2. Rear Display Backlight
3. RS-232 or Relay output Interface



## Specifications:

| Model    | Capacity | Division |
|----------|----------|----------|
| AEP/L-3  | 3kg      | 1g       |
| AEP/L-6  | 6kg      | 1g/2g    |
| AEP/L-15 | 15kg     | 2g/5g    |
| AEP/L-30 | 30kg     | 5g/10g   |

### Power Source:

DC: 4Ah/6V Rechargeable battery  
(160hr without backlight)

AC: 110V or 220V  $\pm$  10%, 50/60Hz

◆ Above is made in Taiwan