

product type designation

product description

PROFIBUS FC bus connector RS 485

Bus connector with axial cable outlet (180°)

PROFIBUS FC RS 485 plug 180 PROFIBUS connector with FastConnect connection plug and axial cable outlet for Industry PC, SIMATIC OP, OLM, Transfer rate: 12 Mbit/s, terminating resistor with isolating function, plastic enclosure.



suitability for use

For connecting PROFIBUS nodes to the PROFIBUS bus cable

transfer rate

transfer rate / with PROFIBUS

9.6 kbit/s ... 12 Mbit/s

interfaces

number of electrical connections

- for PROFIBUS cables
- for network components or terminal equipment

2
1

type of electrical connection

- for PROFIBUS cables
- for network components or terminal equipment

integrated insulation displacement contacts for 2-core PB FC-installation cables
Sub-D connector (9-pin)

type of electrical connection / FastConnect

Yes

mechanical data

design of terminating resistor

Integrated resistor combination that can be selected with slide switch. Disconnect function: When the resistor is connected, the outgoing bus is isolated.

material / of the enclosure

plastic

locking mechanism design

Screwed joint

design, dimensions and weights

type of cable outlet

180° cable outlet

width

16 mm

height

62 mm

depth

34.5 mm

net weight

40 g

ambient conditions

ambient temperature

- during operation
- during storage
- during transport

-40 ... +70 °C
-25 ... +80 °C
-25 ... +80 °C

relative humidity

- at 25 °C / without condensation / during operation / maximum

75 %

protection class IP

IP20

product features, product functions, product components / general

product feature

- silicon-free

Yes

product component

- PG connection socket

No

• strain relief	Yes
standards, specifications, approvals	
certificate of suitability	
• RoHS conformity	Yes
• UL approval	Yes
• cULus approval	Yes
• railway application in accordance with EN 50155	No
further information / internet-Links	
Internet-Link	
• to web page: selection aid TIA Selection Tool	http://www.siemens.com/tia-selection-tool
• to website: Industrial communication	http://www.siemens.com/simatic-net
• to website: Industry Mall	https://mall.industry.siemens.com
• to website: Information and Download Center	http://www.siemens.com/industry/infocenter
• to website: Selection guide for cables and connectors	https://sie.ag/2QdlxcP
• to website: Image database	http://automation.siemens.com/bilddb
• to website: CAX-Download-Manager	http://www.siemens.com/cax
• to website: Industry Online Support	https://support.industry.siemens.com
last modified:	6/30/2021 